







Price List 2011





EUR
V1.0

DISTANCE MEASURING – contactless and reliable

FLS-C – for fast measurements with unique accuracy

Picture	Item No.	Product-ID	Description	Price / EUR
	600502	FLS-C 10	Laser Distance Sensor Measuring range: Natural surfaces: 0.05 ... ~65 m, Reflective foil: 0.5 ... 500 m Accuracy: ±1 mm Measuring rate: up to 20 Hz Operating temperature: -10 °C ... +50 °C (STANDARD) Interfaces: RS-232, RS-422 or SSI, 0/4 ... 20 mA, 3 DO	1350.00
	600501	FLS-C 30	Laser Distance Sensor Measuring range: Natural surfaces: 0.05 ... ~65 m, Reflective foil: 0.5 ... 500 m Accuracy: ±3 mm Measuring rate: up to 20 Hz Operating temperature: -10 °C ... +50 °C (STANDARD) Interfaces: RS-232, RS-422 or SSI, 0/4 ... 20 mA, 3 DO	1190.00
	600504	FLS-CH 10	Laser Distance Sensor Measuring range: Natural surfaces: 0.05 ... ~65 m, Reflective foil: 0.5 ... 500 m Accuracy: ±1 mm Measuring rate: up to 20 Hz Operating temperature: -40 °C ... +50 °C (WITH HEATER) Interfaces: RS-232, RS-422 or SSI, 0/4 ... 20 mA, 3 DO	1450.00
	600503	FLS-CH 30	Laser Distance Sensor Measuring range: Natural surfaces: 0.05 ... ~65 m, Reflective foil: 0.5 ... 500 m Accuracy: ±3 mm Measuring rate: up to 20 Hz Operating temperature: -40 °C ... +50 °C (WITH HEATER) Interfaces: RS-232, RS-422 or SSI, 0/4 ... 20 mA, 3 DO	1320.00

DLS-C – for millimeter precise measuring in extreme situations

Picture	Item No.	Product-ID	Description	Price / EUR
	500622	DLS-C 15	Laser Distance Sensor Measuring range: Natural surfaces: 0.05 ... ~65 m, Reflective foil: 0.5 ... 150 m Accuracy: ±1.5 mm Measuring rate: up to 6 Hz Operating temperature: -10 °C ... +50 °C (STANDARD) Interfaces: RS-232, RS-422, 0/4 ... 20 mA, 3 DO	1170.00
	500621	DLS-C 30	Laser Distance Sensor Measuring range: Natural surfaces: 0.05 ... ~65 m, Reflective foil: 0.5 ... 150 m Accuracy: ±3 mm Measuring rate: up to 6 Hz Operating temperature: -10 °C ... +50 °C (STANDARD) Interfaces: RS-232, RS-422, 0/4 ... 20 mA, 3 DO	1040.00
	500624	DLS-CH 15	Laser Distance Sensor Measuring range: Natural surfaces: 0.05 ... ~65 m, Reflective foil: 0.5 ... 150 m Accuracy: ±1.5 mm Measuring rate: up to 6 Hz Operating temperature: -40 °C ... +50 °C (WITH HEATER) Interfaces: RS-232, RS-422, 0/4 ... 20 mA, 3 DO	1270.00
	500623	DLS-CH 30	Laser Distance Sensor Measuring range: Natural surfaces: 0.05 ... ~65 m, Reflective foil: 0.5 ... 150 m Accuracy: ±3 mm Measuring rate: up to 6 Hz Operating temperature: -40 °C ... +50 °C (WITH HEATER) Interfaces: RS-232, RS-422, 0/4 ... 20 mA, 3 DO	1170.00






Accessories DLS/FLS

Picture	Item No.	Description	Price / EUR
	500590	Starter kit accessories DLS/FLS Consisting of: - RS-232 cable (500200) - Power Supply → Not applicable for measuring devices with the heater! - Utility Software - Manual	100.00
	500001	Calibration certificate for new measuring devices DLS/FLS	90.00
	500002	Recalibration with calibration certificate for used measuring devices DLS/FLS	170.00
	500101	View finder with support for easy adjustment of the sensor, if aiming on targets far away applicable for DLS/FLS	194.00
	500113	Reflective plate 210 x 297 mm (orange) applicable distance range: ~ 25 to 150m	46.00
	500114	Reflective foil 600 x 1200 mm (orange) for self fitting, applicable distance range: ~ 25 to 150m	156.00
	500200	RS-232 Configuration cable DLS/FLS Length = 3m, with 15 pin connector IP65 and 9 pin connector	55.00
	500202	AO/DO Connection cable DLS/FLS Length = 3m, with 15 pin connector IP65	46.00
	500203	RS-422 Connection cable DLS/FLS length = 5m, with 15 pin connector IP65	61.00
	500203/xxx	RS-422 Connection cable - special length Length = XXX m, with 15 pin connector IP65 applicable for DLS/FLS	Price on request
	500210	Converter RS-232 to RS-422 IP20 module, mountable on 35 mm DIN rail applicable for DLS/FLS	138.00
	500213	Alignment jig Adjusting angle +/-7° in two directions Material: stainless steel (V2A) Recommended for distances up to 50m Applicable for EDS/DLS/FLS	49.00





Accessories DLS/FLS

Picture	Item No.	Description	Price / EUR
	500214	DIMS Profibus Interface external Profibus/RS-422 converter, IP20 module, mountable on 35 mm DIN rail applicable for DLS/FLS	335.00
	500215	Numeric digital display 6 digits Char. height 14mm; LED red; RS-232/485; Reading distance: 1...5m applicable for DLS/FLS	272.00
	500251	Cover IP65 for 15 pin D-Sub connector applicable for DLS/FLS	49.00
	500253	Connector 90° IP65 for 15 pin D-Sub connector maximum cable diameter is 5 mm applicable for DLS/FLS	71.00
	500290	Connector straight IP65 for 15 pin D-Sub cable diameter range 6 to 10 mm applicable for DLS/FLS	19.00
	500291	Ferrite for cable diameter 6.5mm	7.00
	500292	Ferrite for cable diameter 10mm	9.00
	500293	Ferrite for cable diameter 13mm	11.00

4. March 2011 / Subject to change without notice

Price List 2011_DLS-C_FLS-C_EUR_EN_V1.odt



GUEMISA (Electrónica Guerra y Miró Guemisa S.L.)
 Sta. Virgilia, 29 - local - 28033 Madrid (Spain)
 Tlfno.: (034) 91 764 21 00 Fax.: (034) 91 764 21 32
 Email.: ventas@guemisa.com Web.: www.guemisa.com

