

HANDHELD DRY-WELLS



your device. The 9100 HDRC has a display resolution of 0.1 degrees, an accuracy of $\pm 0.5^{\circ}\text{C}$ a stability of $\pm 0.1^{\circ}\text{C}$, and a stabilization time of five minutes.

Model 9102 Dry-Well

For work in the temperature range of -10°C to 122°C , Hart's Model 9102 dry-well is another first in the industry.

This dry-well is only 3.25 inches high and 6 inches wide, achieves temperatures as low as -10°C , includes a NIST-traceable calibration, and is accurate to $\pm 0.5^{\circ}\text{C}$. The Model 9102 is excellent for dial gauges, digital thermometers, bulb switches, and other sensors that need calibration below ambient. It's perfect for ISO 9000 quality programs because its calibration is NIST traceable.

It has two wells so you can use one for a reference thermometer to increase accuracy. Both wells are 1/2 inch in diameter, and each has inserts available for almost any sensor size. The 9102 also has a battery pack option that gives you approximately four hours of field use when AC power is unavailable.

Handheld Dry-Well

Models 9100 and 9102

Smallest dry-wells in the world

Fast and easy thermometer checks

Accuracy to $\pm 0.5^{\circ}\text{C}$

RS-232 interface with Hart software (Model 9930)

Hart's line of portable dry-wells is incredible. They're the smallest, lightest, and most portable dry-wells in the world. The Model 9100 weighs only 2 pounds 3 ounces (1 kilogram).

Model 9100 Dry-Well

Since we introduced the world's first truly handheld dry-well, many have tried to duplicate it—in vain. Despite its small size (2 1/4 inches high and 5 inches wide) and light weight, the 9100 outperforms any dry-well in its class in the world.


It's simple and convenient too. Anyone can learn to use one in less than 15 minutes. It has a range to 375°C (707°F) and is perfect for checking RTDs, thermocouples, and small bimetal thermometers in the field.

Plug it in, switch it on, set the temperature with the front-panel buttons, and insert your probe into the properly sized well. Compare the reading of your device to the display temperature or to an external reference, and the difference is the error in



Take the 9100 anywhere. It's the smallest dry-well in the world.

Calibration Wells




Removable insert sleeves
1/2" O.D. x
4" deep

9102 block configuration. Instrument includes 1/4" and 3/16" inserts. Order additional sizes as needed.

Ranges from -10°C to 300°C

Specifications	9100	9102
Range	35°C to 375°C (95°F to 707°F)	-10°C to 122°C (14°F to 252°F) at 23°C ambient
Accuracy	±0.5°C	
Stability	±0.1°C at 100°C ±0.3°C at 375°C	±0.05°C at 0°C ±0.1°C at 122°C
Well-to-Well Uniformity	±0.2°C with sensors of similar size at equal depths within wells	
Heating Times	35° to 375°C: 9.5 minutes	ambient to 100°C: 10 minutes
Stabilization	5 minutes	7 minutes
Cooling Times	375°C to 100°C: 14 minutes	ambient to 0°C: 10 minutes
Well Depth	4 inches (102 mm); 1/16" (1.6 mm) hole is 3.5" (89 mm) deep	4 inches (102 mm)
Removable Inserts	N/A	Available in sizes from 1/16" (1.6 mm) to 7/16" (11.1 mm) [1/4" (6.4 mm) and 3/16" (4.8 mm) included]
Computer Interface	RS-232 included with free Interface- <i>it</i> software (model 9930)	
Power	115 VAC (±10%), 1.5 A or 230 VAC (±10%), 0.8 A, specify, 50/60 Hz, 175 W	94-234 VAC (±10%), 50/60 Hz, 60 W; or 12 VDC
Size	2.25" H x 4.9" W x 5.9" D (57 x 125 x 150 mm)	3.9" H x 5.5" W x 6.9" D (99 x 140 x 175 mm)
Weight	2 lb. 3 oz. (1 kg)	4 lb. (1.8 kg)
NIST-Traceable Calibration	Data at 50°C, 100°C, 150°C, 200°C, 250°C, 300°C, and 350°C	Data at -10°C, 25°C, 50°C, 55°C, 100°C, and 122°C

9100 Fixed-Block Options



9100 fixed-block options. Order number HT9100S-A or HT9100S-D for the desired block option.



Model 9102 shown with battery pack, which includes a battery, carrying bag, cables, and charger.

Ordering Information

- HT9100S-A-156** Dry-Well, 110V 50/60Hz Handheld Block A
- HT9100S-A-256** Dry-Well, 220V 50/60Hz Handheld Block A
- HT9100S-D-156** Dry-Well, 110V 50/60Hz Handheld Block D
- HT9100S-D-256** Dry-Well, 220V 50/60Hz Handheld Block D
- HT9300** Case, 9100 Rugged Carrying

Ordering Information

- HT9102S-156** Dry-Well, 110 V, 50/60 Hz, -10 to 122 (2 Wells)
- HT9102S-256** Dry-Well, 220 V, 50/60 Hz, -10 to 122 (2 Wells)
- HT9312** Battery Pack, 9102
- HT9308** Case, Hard Carrying
- HT3102-1** Insert, AL 1/16 inch
- HT3102-2** Insert, AL 1/8 inch
- HT3102-3** Insert, AL 3/16 inch
- HT3102-4** Insert, AL 1/4 inch
- HT3102-6** Insert, AL 3/8 inch



Sta. Virgilia 29 Local.1A 28033 Madrid
Tfno.: 91 764 21 00 Fax.: 91 764 21 32
www.guemisa.com Email.:info@guemisa.com

For more information about this Hart Scientific product, contact your local Fluke distributor.
To locate your nearest Fluke distributor, go to www.fluke.com or call 1-800-44-FLUKE or 425-446-5500.